

AutomationDirect » STRIDE Ethernet Switches



SE2-SW16M



SE-SL3011



SE2-SW5U



SE2-SW8U

Part Number	
STRIDE - Industrial Unmanaged Ethernet Media Converters (DIN Rail, Hazardous Location Rated)	
SE2-MC2U-C1-T	2 ports, (1) RJ45 10/100 and (1) multi-mode SC 100FX fiber port(s), -40 to +75 deg C, metal housing, IP30
SE2-MC2U-C1-T	2 ports, (1) RJ45 10/100 and (1) multi-mode SC 100FX fiber port(s), -40 to +75 deg C, metal housing, IP30
SE-MC2U-SC	2 ports, (1) RJ45 10/100 and (1) multi-mode SC 100FX fiber ports, -10 to +60 deg C, plastic housing, IP40
SE2-MC2U-T1-T	2 ports, (1) RJ45 10/100 and (1) multi-mode ST 100FX fiber port(s), -40 to +75 deg C, metal housing, IP30
SE-MC2U-ST	2 ports, (1) RJ45 10/100 and (1) multi-mode ST 100FX fiber ports, -10 to +60 deg C, plastic housing, IP40
STRIDE - Industrial Unmanaged Ethernet Switches	
SE2-SW5U	5 ports, (5) RJ45 10/100 ports, -10 to +60 deg C, metal housing, IP30, 35mm DIN rail mount, hazardous location rated.
SE-SW5U	5 ports, (5) RJ45 10/100 ports, -10 to +60 deg C, plastic housing, IP40, DIN rail mount, haz rated
SE2-SW5U-T	5 ports, (5) RJ45 10/100 ports, -40 to +75 deg C, metal housing, IP30, DIN rail mount, haz rated
SE-SW5U-WT	5 ports, (5) RJ45 10/100 ports, -40 to +85 deg C, metal housing, IP40, DIN rail mount, haz rated
SE2-SW5U-1C1-T	5 ports, (4) RJ45 10/100 and (1) multi-mode SC 100FX fiber port(s), -40 to +75 deg C, metal housing, IP30, DIN rail mount, haz rated
SE-SW5U-SC	5 ports, (4) RJ45 10/100 and (1) multi-mode SC 100FX fiber ports, -10 to +60 deg C, plastic housing, IP40, DIN rail mount, haz rated
SE-SW5U-SC-WT	5 ports, (4) RJ45 10/100 and (1) multi-mode SC 100FX fiber ports, -40 to +85 deg C, metal housing, IP40, DIN rail mount, haz rated
SE2-SW5U-1T1-T	5 ports, (4) RJ45 10/100 and (1) multi-mode ST 100FX fiber port(s), -40 to +75 deg C, metal housing, IP30, DIN rail mount, haz rated
SE-SW5U-ST	5 ports, (4) RJ45 10/100 and (1) multi-mode ST 100FX fiber ports, -10 to +60 deg C, plastic housing, IP40, DIN rail mount, haz rated
SE-SW5U-ST-WT	5 ports, (4) RJ45 10/100 and (1) multi-mode ST 100FX fiber ports, -40 to +85 deg C, metal housing, IP40, DIN rail mount, haz rated
SE2-SWP5U-T	5 ports, (4) RJ45 10/100 POE+ and (1) RJ45 10/100 port(s), 48 VDC nominal input, -40 to +75 deg C, metal housing, IP30, DIN rail mount, haz rated
SE2-SWP5UG-T	5 ports, (4) RJ45 Gigabit POE+ and (1) RJ45 Gigabit port(s), 48 VDC nominal input, -40 to +75 deg C, metal housing, IP30, DIN rail mount, haz rated
SE2-SW5U-N65-T	5 ports, (5) M12 10/100 ports, -40 to +75 deg C, metal housing, IP65, panel mount.
SE2-SW5UG-T	5 ports, (5) RJ45 Gigabit ports, -40 to +75 deg C, metal housing, IP30, DIN rail mount, haz rated
SE2-SW8U	8 ports, (8) RJ45 10/100 ports, -10 to +60 deg C, metal housing, IP30, DIN rail mount, haz rated
SE-SW8U	8 ports, (8) RJ45 10/100 ports, -10 to +60 deg C, plastic housing, IP40, DIN rail mount, haz rated
SE2-SW8U-T	8 ports, (8) RJ45 10/100 ports, -40 to +75 deg C, metal housing, IP30, DIN rail mount, haz rated
SE-SW8U-WT	8 ports, (8) RJ45 10/100 ports, -40 to +85 deg C, metal housing, IP40, DIN rail mount, haz rated
SE2-SW8U-2C1-T	8 ports, (6) RJ45 10/100 and (2) multi-mode SC 100FX fiber ports, -40 to +75 deg C, metal housing, IP30, DIN rail mount, haz rated
SE2-SW8U-2T1-T	8 ports, (6) RJ45 10/100 and (2) multi-mode ST 100FX fiber ports, -40 to +75 deg C, metal housing, IP30, DIN rail mount, haz rated
SE2-SW8U-N65-T	8 ports, (8) M12 10/100 ports, -40 to +75 deg C, metal housing, IP65, panel mount.
SE2-SW8UG-T	8 ports, (8) RJ45 Gigabit ports, -40 to +75 deg C, metal housing, IP30, DIN rail mount, haz rated
SE-SW9U-SC	9 ports, (8) RJ45 10/100 and (1) multi-mode SC 100FX fiber ports, -10 to +60 deg C, plastic housing, IP40, DIN rail mount, haz rated
SE-SW9U-SC-WT	9 ports, (8) RJ45 10/100 and (1) multi-mode SC 100FX fiber ports, -40 to +85 deg C, metal housing, IP40, DIN rail mount, haz rated
SE-SW9U-ST	9 ports, (8) RJ45 10/100 and (1) multi-mode ST 100FX fiber ports, -10 to +60 deg C, plastic housing, IP40, DIN rail mount, haz rated
SE-SW9U-ST-WT	9 ports, (8) RJ45 10/100 and (1) multi-mode ST 100FX fiber ports, -40 to +85 deg C, metal housing, IP40, DIN rail mount, haz rated
SE2-SW16U-T	16 ports, (16) RJ45 10/100 ports, -40 to +75 deg C, metal housing, IP30, DIN rail mount, haz rated
SE2-PM1	STRIDE panel mounting bracket, for use with SE2-SW5U(-T), SE2-SW5UG-T & SE2-SW8U(-T) Ethernet switches.
SE2-PM3	STRIDE panel mounting bracket, for use with SE2-SW8UG-T, SE2-SW10UG-2P-T, SE2-SW16U-T & all SE2 series managed Ethernet switches.