

# AutomationDirect » Fuji Molded Case

Fuji Circuit Breakers	Molded Case UL489 3-Pole Line and Load Lugs included Non-Adjustable Thermal magnetic trip		Accessories - Not Pre-Installed - Sold Separately
BW125JAGU-3P015SB	15A, 240/480/600VAC & 250VDC		BW125 & BW250 Frame Accessory Selection Guide
BW125JAGU-3P020SB	20A, 240/480/600VAC & 250VDC	BW9W1SG0	Field installable Auxiliary Contact - SPDT - 20AWG - 19.69" leads - Left side mount only
BW125JAGU-3P030SB	30A, 240/480/600VAC & 250VDC	BW9FRG0	Field installable DC shunt trip - 24VDC/AC, 20AWG - 19.69" leads - left & right side mount
BW125JAGU-3P040SB	40A, 240/480/600VAC & 250VDC	BW9FAG0	Field installable AC shunt trip - 100-120VAC, 20AWG - 19.69" leads - left & right side mount
BW125JAGU-3P050SB	50A, 240/480/600VAC & 250VDC	BW9RGAR	Field installable DC undervoltage release - 24VDC, 20AWG - 19.69" leads - left side mount only
BW125JAGU-3P060SB	60A, 240/480/600VAC & 250VDC	BW9RGAT	Field installable AC undervoltage release - 110-130VAC - 20AWG - 19.69" leads - left side mount only
BW125JAGU-3P070SB	70A, 240/480/600VAC & 250VDC	BW9V0CA	NEMA 12 rotary handle for BW125-Frame. Position indicating; lock-off feature. Shaft length 0.39"
BW125JAGU-3P075SB	75A, 240/480/600VAC & 250VDC	BW9V0GA	NEMA 12 rotary handle for BW250-Frame. Position indicating; lock-off feature. Shaft length 0.39"
BW125JAGU-3P080SB	80A, 240/480/600VAC & 250VDC	BW9VSG0	NEMA 12 rotary handle for BW9V0CA & BW9V0GA. Steel shaft length 6.06"
BW125JAGU-3P090SB	90A, 240/480/600VAC & 250VDC	BW9VSG0-24	NEMA 12 rotary handle for BW9V0CA & BW9V0GA. Steel shaft length 24"
BW125JAGU-3P100SB	100A, 240/480/600VAC & 250VDC	BW9F0CA-15A	NEMA 12 flexible shaft handle for BW125-Frame - Flange mount - Lockable - Flex cable shaft length - 1.5m
BW125JAGU-3P125SB	125A, 240/480/600VAC & 250VDC	BW9F0CA-20A	NEMA 12 flexible shaft handle for BW125-Frame - Flange mount - Lockable - Flex cable shaft length - 2m
BW250JAGU-3P125SB	125A, 240/480/600VAC & 250VDC	BW9F0GA-15A	NEMA 12 flexible shaft handle for BW250-Frame - Flange mount - Lockable - Flex cable shaft length - 1.5m
BW250JAGU-3P150SB	150A, 240/480/600VAC & 250VDC	BW9F0GA-20A	NEMA 12 flexible shaft handle for BW250-Frame - Flange mount - Lockable - Flex cable shaft length - 2m
BW250JAGU-3P160SB	160A, 240/480/600VAC & 250VDC	BW9Q1CA	Lockout attachment for BW125/250 series MCCBs. Lock not included.
BW250JAGU-3P175SB	175A, 240/480/600VAC & 250VDC		
BW250JAGU-3P200SB	200A, 240/480/600VAC & 250VDC		
BW250JAGU-3P225SB	225A, 240/480/600VAC & 250VDC		
BW250JAGU-3P250SB	250A, 240/480/600VAC & 250VDC		
			<b>BW400, 630 &amp; 800 Frame Accessory Selection Guide</b>
BW400SAGU-3P250SB	250A, 240/480VAC & 250VDC	BW9W1SHA	Field installable Auxiliary Contact - SPDT - 20AWG - 19.69" leads - Left side mount only
BW400SAGU-3P300SB	300A, 240/480VAC & 250VDC	BW9FHA-R	Field installable DC shunt trip - 24VDC/AC, 20AWG - 19.69" leads - left & right side mount
BW400SAGU-3P350SB	350A, 240/480VAC & 250VDC	BW9FHA-A	Field installable AC shunt trip - 100-120VAC, 20AWG - 19.69" leads - left & right side mount
BW400SAGU-3P400SB	400A, 240/480VAC & 250VDC	BW9RHA-R	Field installable DC undervoltage release - 24VDC, 20AWG - 19.69" leads - left side mount only
BW630RAGU-3P500SB	500A, 240/480VAC & 250VDC	BW9RHA-1	Field installable AC undervoltage release - 110-130VAC - 20AWG - 19.69" leads - left side mount only
BW630RAGU-3P600SB	600A, 240/480VAC & 250VDC	BW9BTHA-L3W	Terminal Cover for BW400-frame MCCBs, line and load side, package of 2
BW800RAGU-3P700SB	700A, 240/480VAC & 250VDC	BW9BTJA-L3W	Terminal Cover for BW630 & 800-frame MCCBs, line and load side, package of 2
BW800RAGU-3P800SB	800A, 240/480VAC & 250VDC	BW9V0HA	NEMA 12 rotary handle for BW400-Frame. Position indicating; lock-off feature. Shaft length 0.39"
		BW9V0JA	NEMA 12 rotary handle for BW630 & 800 Frame. Position indicating; lock-off feature. Shaft length 0.39"
		BZ-VS2	NEMA 12 rotary handle shaft for BW400,630,&800-frames. Steel shaft length: 3.48"
		BZ-VS2-24	NEMA 12 rotary handle shaft for BW400,630,&800-frames. Steel shaft length: 24"
		BW9F0HA-15A	NEMA 12 flexible shaft handle for BW400-Frame - Flange mount - Lockable - Flex cable shaft length - 1.5m
		BW9F0HA-20A	NEMA 12 flexible shaft handle for BW400-Frame - Flange mount - Lockable - Flex cable shaft length - 2m
		BW9F0JA-15A	NEMA 12 flexible shaft handle for BW630/800-Frame - Flange mount - Lockable - Flex cable shaft length - 1.5m
		BW9F0JA-20A	NEMA 12 flexible shaft handle for BW630/800-Frame - Flange mount - Lockable - Flex cable shaft length - 2m
		BW9QNHA	Lockout attachment for BW400/630/800 series MCCBs. Lock not included.

